



Main

Range	EasyLogic
Product name	EasyLogic DM6X00H RS
Device short name	DM6200H
Product or component type	VAF PF meter

Complementary

Device application	Remote monitoring
Type of measurement	Current Voltage Frequency RPM
Metering type	Unbalance current Rotation speed Average current Iavg Average voltage Vavg Unbalance voltage Phase currents Frequency Calculated neutral current Voltage U21, U32, U13, V1, V2, V3
Counter functions	ON hour counting Power interruption
[Us] rated supply voltage	48...277 V AC 45...65 Hz 48...277 V DC
Network frequency	60 Hz 50 Hz
[In] rated current	1 A 5 A
Type of network	3P + N 3P 1P + N 2P + N 2P

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum power consumption in VA	4 VA at 240 V between phase and neutral
Maximum power consumption in W	2 W at 240 V
Display type	8 segments LED
Display colour	Red
Messages display capacity	3 fields of 4 characters
Display digits	12 digit(s) - 14.2 mm in height
Communication of data	Instantaneous and demand values Revolution speed All counters Reading of measurements
Tamperproof of settings	Protected by access code
Sampling rate	32 samples/cycle
Measurement current	5...6000 mA
Signal	Current 0.005...10 A (impedance 0.3 MOhm)6 x
Measurement voltage	46...277 V AC 50...60 Hz between phase and neutral 80...480 V AC 50...60 Hz between phases 277...999000 V AC 50...60 Hz with external VT
Frequency measurement range	45...65 Hz
Number of inputs	2
Measurement accuracy	Frequency +/- 0.05 % Power factor +/- 0.01 Current +/- 1 % Voltage +/- 1 %
Accuracy class	Class 1
Demand intervals	1 s
Local signalling	Green LED: activity Red LED: output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh)
Communication port protocol	Modbus at 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2-wire, insulation 2500 V
Communication port support	Screw terminal block: RS485
Material	Polycarbonate
Flame retardance	V-0 conforming to UL 94
Mounting mode	Flush-mounted
Mounting support	Framework
Installation category	III
Type of installation	Indoor installation
Measurement category	Category III 480 V
Electrical insulation class	Class II
Connections - terminals	Current circuit: screw clamp terminals (bottom) 2.08...3.31 mm ² cable(s) Voltage circuit: screw clamp terminals (top) 0.82...3.31 mm ² cable(s) Control circuit: screw clamp terminals (top) 0.82...3.31 mm ² cable(s) Communication: screw clamp terminals (bottom) 0.33...3.31 mm ² cable(s)
Tightening torque	Current circuit: 0.9...1 N.m Philips No 2 screwdriver Voltage circuit: 0.9...1 N.m Philips No 2 screwdriver Control circuit: 0.9...1 N.m Philips No 2 screwdriver Communication: 0.5...0.6 N.m Philips no 1 screwdriver
Wire stripping length	Current circuit: 3.68 mm Voltage circuit: 7 mm Control circuit: 7 mm Communication: 7 mm
Standards	IEC 61010-1:ed. 3 UL 61010-1:ed. 3
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 C-Tick
Width	96 mm
Depth	13 mm outside: 49 mm panel:
Height	96 mm
Net weight	300 g

Environment

Electromagnetic compatibility	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 class A Emission tests conforming to FCC part 15 subpart C Emission tests conforming to FCC part 15 subpart E
Overvoltage category	III
IP degree of protection	IP51 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529
Relative humidity	5...95 % at 50 °C
Pollution degree	2
Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Operating altitude	<= 2000 m
Service life	7 year(s)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information