



### Main

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| Range                       | Mini Pragma                                   |
| Product or component type   | Enclosure                                     |
| Enclosure type              | Modular enclosure                             |
| Nb of 18 mm modules per row | 12                                            |
| Nb of horizontal rows       | 2                                             |
| Type of door                | Translucid                                    |
| Width                       | 270 mm wall:<br>294 mm outside:               |
| Height                      | 353 mm wall:<br>377 mm outside:               |
| Depth                       | 18 mm outside:<br>80 mm wall:<br>98 mm total: |
| Built-in depth              | 80 mm                                         |

### Complementary

|                               |                                                                                                                                                |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Enclosure mounting            | Flush                                                                                                                                          |
| 9 mm pitches                  | 24                                                                                                                                             |
| Total number of 18 mm modules | 24                                                                                                                                             |
| [In] rated current            | 63 A                                                                                                                                           |
| Type of rail                  | 35 mm asymmetrical rail                                                                                                                        |
| Mounting plate description    | Without mounting plate                                                                                                                         |
| Cable entry                   | Pre-cutted holes                                                                                                                               |
| Terminal block function       | Earth / neutral                                                                                                                                |
| Number of terminal blocks     | 1 earth (screwed) with 16 outgoers<br>1 neutral (screwed) with 16 outgoers                                                                     |
| Distribution block outgoers   | 2 x 16 mm <sup>2</sup> for earth<br>2 x 16 mm <sup>2</sup> for neutral<br>6 x 6 mm <sup>2</sup> for earth<br>6 x 6 mm <sup>2</sup> for neutral |

|                    |                                                                              |
|--------------------|------------------------------------------------------------------------------|
|                    | 8 x 10 mm <sup>2</sup> for earth<br>8 x 10 mm <sup>2</sup> for neutral       |
| Enclosure material | Back part: technoplastic<br>Door: technoplastic<br>Front face: technoplastic |
| Internal depth     | 76 mm                                                                        |
| Colour             | Front face: white (RAL 9003)<br>Door: translucid                             |

## Environment

|                                       |                                                                      |
|---------------------------------------|----------------------------------------------------------------------|
| Standards                             | IEC 60695-2-11<br>IEC 60670-24<br>EN 50102<br>IEC 529<br>IEC 60439-3 |
| Quality labels                        | IMQ                                                                  |
| Fire resistance                       | Door: 650 °C<br>Back part: 650 °C<br>Front face: 650 °C              |
| IP degree of protection               | IP40                                                                 |
| IK degree of protection               | IK07                                                                 |
| Ambient air temperature for operation | -25...60 °C                                                          |

## Offer Sustainability

|                            |                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                 |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                     |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| Mercury free               | Yes                                                                                                                   |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                         |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|