PRODUCT-DETAILS

# S2C-S/H6R

# S2C-S/H6R - Signal / Auxiliary Contact



## General Information

| | |
|---|---|
| Extended Product Type | S2C-S/H6R |
| Product ID | 2CDS200922R0001 |
| EAN | 4016779563819 |
| Catalog Description | S2C-S/H6R - Signal / Auxiliary Contact |
| Long Description | Choice through a selector between indication of the position of the device's contacts and signalling of a fault (overcurrent/short-circuit for MCBs and RCBOs, earth fault for RCCBs and RCBOs). Suitable for MCBs S 200 series, SN 201 series, RCCBs F 200 series, RCBOs DS201, DS202C, DS 200 series. |

## Ordering

| | |
|---|---|
| E-Number (Finland) | 3210835 |
| E-Number (Sweden) | 2102501 |
| EAN | 4016779563819 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |

## Dimensions

| | |
|---|---|
| Product Net Width | 8.8 mm |
| Product Net Height | 85 mm |

| | |
|---|---|
| Product Net Depth / Length | 69 mm |
| Product Net Weight | 0.043 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 20 mm |
| Package Level 1 Height | 115 mm |
| Package Level 1 Depth / Length | 104 mm |
| Package Level 1 Gross Weight | 0.045 kg |
| Package Level 1 EAN | 4016779678872 |
| Package Level 2 Units | 60 piece |
| Package Level 2 Width | 275 mm |
| Package Level 2 Height | 210 mm |
| Package Level 2 Depth / Length | 395 mm |
| Package Level 2 Gross Weight | 3.4 kg |
| Package Level 2 EAN | 4016779946209 |

## Environmental

| | |
|---|---|
| RoHS Status | Following EU Directive 2011/65/EU |

## Additional Information

| | |
|---|---|
| Function | Signal / Auxiliary Contact |
| Power Loss | 0.5 W<br>Maximum 0.5 W |
| Product Main Type | S2C |
| Product Name | Signal / Auxiliary Contact |
| RoHS Date | 0335 |
| Standards | CSA 22.2 No. 235<br>GB/T 14048.5<br>IEC/EN 60947-5-1<br>UL 1077 |
| Suitable For | S200<br>S200M<br>S200P<br>S200S<br>SN201L+SN201-IH<br>SN201+SN201-IH<br>SN201M+SN201-IH<br>F200<br>DS201<br>DS202C<br>DS200<br>S-ARC1<br>DS-ARC1 |
| Suitable for Product Class | Miniature Circuit Breaker<br>Residual Current Device |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| Data Sheet, Technical Information | 9AKK106930A8017 |
| Declaration of Conformity - CE | 2CDK400629D2701 |
| Instructions and Manuals | 9AKK107680A3432 |
| RoHS Information | 2CDK440032D0203 |

## Classifications

| | |
|---|---|
| ETIM 4 | EC001286 - Auxiliary contact unit for distribution board |
| ETIM 5 | EC001286 - Auxiliary contact unit for distribution board |
| ETIM 6 | EC001286 - Auxiliary contact unit for distribution board |
| ETIM 7 | EC001286 - Auxiliary device for distribution board devices |
| UNSPSC | 39121614 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.0 : 27143502 |

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs Accessories → Auxiliary / Signal Contacts

Low Voltage Products and Systems → Modular DIN Rail Products → Protection Against Arc Faults AFDDs Accessories → Accessoreis for Arc Fault Detection Devices with Integrated Overcurrent and Residual Current Protection - AFDD+RCBO

Low Voltage Products and Systems → Modular DIN Rail Products → Protection Against Arc Faults AFDDs Accessories → Accessories for Arc Fault Detection Devices with Integrated Overcurrent Protection - AFDD+MCB

