

PRODUCT-DETAILS

OTM400E3M230C

OTM400E3M230C MOTORIZED SWITCH



General Information

Extended Product Type	OTM400E3M230C
Product ID	1SCA115333R1001
EAN	6417019477114
Catalog Description	OTM400E3M230C MOTORIZED SWITCH
Long Description	3-pole, motor operated, base mounted switch-d disconnecter with handle for manual operation, terminal bolt kit, handle and spare fuse storage clip and male connector for control circuit

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC303006M0205

Dimensions

Product Net Width	342 mm
-------------------	--------

Product Net Height	185 mm
Product Net Depth / Length	211.5 mm
Product Net Weight	7.6 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A (1000 V AC) 400 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 132 kW (400 ... 415 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 400 A
Conventional Thermal Current (I_{the})	Fully Enclosed 400 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 65 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 15 kA
Motor Operational Voltage	220 ... 240 V AC
Power Loss	at Rated Operating Conditions per Pole 10 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 30..44 N·m
Mechanical Durability	16000
Lock Type	Yes

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301198D0202
Instructions and Manuals	1SCC303006M0205
RoHS Information	1SCC303036D0202

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	255 mm
Package Level 1 Depth / Length	460 mm
Package Level 1 Height	253 mm
Package Level 1 Gross Weight	9.2 kg
Package Level 1 EAN	6417019477114

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3638148

Categories

Low Voltage Products and Systems → Switches → Motorized Switch-Disconnectors

