


PRODUCT-DETAILS

# OTM2500E3M230C

## OTM2500E3M230C MOTORIZED SWITCH



### General Information

Extended Product Type	OTM2500E3M230C
Product ID	1SCA115373R1001
EAN	6417019477435
Catalog Description	OTM2500E3M230C MOTORIZED SWITCH
Long Description	3-pole, motor operated, base mounted switch-disconnector with handle for manual operation, terminal bolt kit, handle and spare fuse storage clip and male connector for control circuit

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC303006M0205

---

## Dimensions

Product Net Width	644.5 mm
Product Net Height	376.4 mm
Product Net Depth / Length	153 mm
Product Net Weight	32.7 kg 72 lb

---



---

## Technical

Rated Operational Current AC-22B ( $I_e$ )	(380 ... 415 V) 2500 A (500 V) 2500 A (690 V) 2500 A
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 2500 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 176 kA
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 55 kA
Motor Operational Voltage	220 ... 240 V AC
Power Loss	at Rated Operating Conditions per Pole 85 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 50...75 N·m
Mechanical Durability	6000
Lock Type	Yes

---



---

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

---

## Certificates and Declarations (Document Number)

---

Declaration of Conformity - CE	1SCC301241D2701
Instructions and Manuals	1SCC303006M0205
RoHS Information	1SCC301241D2701

---



---

## Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	435 mm 17.1 in
Package Level 1 Depth / Length	673 mm 26.5 in
Package Level 1 Height	215 mm 8.5 in
Package Level 1 Gross Weight	35.1 kg 77.3 lb
Package Level 1 EAN	6417019477435

---



---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3638162

---



---

## Categories

---

Low Voltage Products and Systems → Switches → Motorized Switch-Disconnectors

