

# Product data sheet

Specifications



## Circuit breaker ComPacT NSXm H (70kA at 415VAC), 3 Poles 3d, 16A rating TMD trip unit, EverLink connectors

C11H3TM016L

### Main

Range	ComPacT new generation
Product name	ComPacT NSXm new generation
Range of product	ComPacT NSXm new generation
Device short name	NSXm 100H
Product or component type	Circuit breaker
Device application	Protection Distribution
Poles description	3P
Protected poles description	3D
[In] rated current	16 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	100 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 70 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 30 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 22 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 10 kA Icu at 660...690 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	H 70 kA 415 V AC
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle
Circuit breaker mounting mode	Fixed

### Complementary

[Ui] rated insulation voltage	800 V
[Uimp] rated impulse withstand voltage	8 kV

<b>[Ics] rated service short-circuit breaking capacity</b>	100 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 70 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 30 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 22 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 2.5 kA at 660...690 V AC 50/60 Hz conforming to IEC 60947-2
<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	20000 cycles at 440 V In/2 10000 cycles at 440 V In 10000 cycles at 690 V In/2 5000 cycles at 690 V In
<b>Power losses</b>	2.4 W
<b>Mounting support</b>	Backplate
<b>Upside connection</b>	Front
<b>Downside connection</b>	Front
<b>Connection terminals</b>	1 Everlink lug wire size 2.5...95 mm <sup>2</sup> , rigid or stranded aluminium/copper 1 Everlink lug wire size 2.5...70 mm <sup>2</sup> , flexible copper
<b>Connection pitch</b>	35 mm with spreaders 27 mm without spreaders
<b>9 mm pitches</b>	9 module
<b>Trip unit rating</b>	16 A at 40 °C
<b>Long-time pick-up adjustment type Ir (thermal protection)</b>	Adjustable
<b>[Ir] long-time protection pick-up adjustment range</b>	0.7...1 x In
<b>Long-time protection delay adjustment type tr</b>	Fixed
<b>[Im] magnetic protection pick-up range</b>	500 A
<b>Short-time protection pick-up adjustment type Isd</b>	Fixed
<b>Short-time protection delay adjustment type tsd</b>	Fixed
<b>Number of slots for electrical auxiliaries</b>	1 slot(s) for auxiliary switch OF 1 slot(s) for alarm switch SD 1 slot(s) for voltage release MN or MX
<b>Local signalling</b>	Flag (green) for presence of auxiliary contacts
<b>Width (W)</b>	81 mm
<b>Height (H)</b>	137 mm
<b>Depth (D)</b>	80 mm
<b>Product weight</b>	1.06 kg
<b>Quantity per set</b>	Set of 1
<b>Colour</b>	Grey (RAL 7016)

## Environment

<b>Standards</b>	EN/IEC 60947
<b>Pollution degree</b>	3 conforming to IEC 60664-1
<b>IP degree of protection</b>	IP40
<b>IK degree of protection</b>	IK07 conforming to IEC 62262
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-50...85 °C
<b>Operating altitude</b>	2000 m without derating

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	1.3 kg
<b>Package 1 Height</b>	9 cm
<b>Package 1 width</b>	13 cm
<b>Package 1 Length</b>	22 cm
<b>Unit Type of Package 2</b>	P12
<b>Number of Units in Package 2</b>	216
<b>Package 2 Weight</b>	304.89 kg
<b>Package 2 Height</b>	150 cm
<b>Package 2 width</b>	80 cm
<b>Package 2 Length</b>	120 cm
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	9
<b>Package 3 Weight</b>	12.29 kg
<b>Package 3 Height</b>	30 cm
<b>Package 3 width</b>	30 cm
<b>Package 3 Length</b>	40 cm

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>