

# Product data sheet

Specifications



## standard motor mechanism module MT250, ComPact NSX250, 250 VDC

LV431546

### Main

Device short name	MT250
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPact NSX250 Compact NSX250 DC PowerPact Multistandard EasyPact CVS250 PowerPact J PowerPact H
Control type	Standard
[Uc] control circuit voltage	250 V DC
Circuit breaker mounting mode	Fixed
Circuit breaker frame rated current	250 A

### Complementary

Control signal type	Impulse Maintained
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	1 to 3 padlocks Ø 5 to Ø 8 Padlocking in OFF position

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.41 kg
Package 1 Height	12.1 cm
Package 1 width	10.4 cm
Package 1 Length	17.4 cm
Unit Type of Package 2	S04
Number of Units in Package 2	15

Package 2 Weight	21.425 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

Warranty	18 months
----------	-----------